






Lubricador NPT 1/8...2

Modelo C: policarbonato con protección (presión máx.: 1,0 MPa/150 psi)

	TAMAÑO	MODELO MICRO NIEBLA(2)	MICRO NIEBLA (2)	TAMAÑO PUERTO (1)	FLUJO (CFM)	CAPACIDAD DE LA TAZA DE ACEITE (ML)
	Compacto	4ZL56	-	1/8	10	20
		4ZL57	-	1/4	14	20
	Intermedia	4ZL69	4ZL65	1/4	51	45
		4ZL71	4ZL67	3/8	51	45
	Estándar	4ZL79	4ZL73	1/4	60	780
		4ZL81	4ZL75	3/8	60	80
		4ZL83	4ZL77	1/2	60	80
	Servicio Pesado	4ZL91	4ZL85	3/8	114	150
		4ZL93	4ZL87	1/2	154	150
		4ZL95	4ZL89	3/4	142	150

Modelo M: metal con mirilla (presión máx.: 1,7 MPa/250 psi)

	TAMAÑO	MODELO MICRO NIEBLA(2)	MICRO NIEBLA (2)	TAMAÑO PUERTO (1)	FLUJO (CFM)	CAPACIDAD DE LA TAZA DE ACEITE (ML)
	Compact	4ZL68	4ZL64	1/4	51	80
		4ZL70	4ZL66	3/8	51	80
	Intermedia	4ZL78	4ZL72	1/4	60	85
		4ZL80	4ZL74	3/8	60	85
		4ZL82	4ZL76	1/2	60	85
	Estándar	4ZL90	4ZL84	3/8	114	155
		4ZL92	4ZL86	1/2	154	155
		4ZL94	4ZL88	3/4	142	155
	Servicio Pesado	4ZL58	4ZL59	3/4	160	750
		4ZL60	4ZL61	1	275	750
		4ZL62	4ZL63	1-1/2	275	750

(1): La rosca estándar es NPT, para rosca G y PT es opcional.

(2): Con micro niebla, el aceite se puede inyectar con 12-15 metros, y con niebla normal, la inyección de aceite es de 4,5-6 metros.