

How to Order

AC **30** **A** - **03** **DG** - **03** - **03** - **A**

q w e r t y

• Option/Semi-standard: Select one each for a to l.
• Option/Attachment/Semi-standard symbol: When more than one specification is required, indicate in alphanumeric order.
Example) AC30A-F03DM-KSV-13NR-A

		Symbol	Description	q				
				Body size				
				20	30	40		
w	Thread type	Nil	Rc					
		N	NPT					
		F	G					
		+						
e	Port size	01	1/8			—		
		02	1/4					
		03	3/8	—				
		04	1/2	—	—			
		06	3/4	—	—			
		+						
r	Option 1)	a	Float type auto drain	Nil	Without auto drain			
			C ^{Note 2)}	N.C. (Normal close) Drain port is closed when pressure is not applied.				
			D ^{Note 3)}	N.O. (Normal open) Drain port is open when pressure is not applied.	—			
		+						
	b	Pressure gauge ^{Note 4)}	Nil	Without pressure gauge				
			G	Round type pressure gauge (with limit indicator)				
			M	Round type pressure gauge (with color zone)				
		+						
t	Attachment	c	Check valve	Nil	Without attachment			
				K	Mounting position: AW+K+AL			Note 5)
				+				
		d	Pressure switch	Nil	Without attachment			
				S ^{Note 6)}	Mounting position: AW+S+AL			
		+						
	e	3-port valve for residual pressure release	Nil	Without attachment				
			V	Mounting position: AW+AL+V				
		+						
y	Semi-standard	f	Set pressure ^{Note 7)}	Nil	0.05 to 0.7 MPa setting			
				1	0.02 to 0.2 MPa setting			
				+				
		g	Bowl	Nil	Polycarbonate bowl			
				C	With bowl guard		—	—
				+				
		h	Filter regulator drain port	Nil	With drain cock			
				J ^{Note 8)}	Drain guide 1/8		—	—
					Drain guide 1/4	—		
				W	Drain cock with barb fitting (for ø6 x ø4 nylon tube)	—		